



Application

The 26.5 mm Signal Cartridge provides high intensity localized signalling for ground and sea operations. May be carried in aircraft for safety.

Description

The 26.5mm signal cartridge is a smaller calibre item used in the role of short range signalling and illumination.

Operation

The round is loaded and fired vertically in the conventional way from a suitable 26.5mm weapon.

Specifications

Length: 68mm
 Diameter: 26.5mm
 Height (vertical): 76m minimum
 Burn time: 6 secs minimum
 Light intensity peak (candela):
 Illuminating: 45,000
 Red: 35,000
 Green: 30,000
 Yellow: 40,000
 White: 40,000
 Overall weight: 50g nominal
 N.E.Q.: 20g nominal

References:

Product Codes: **NATO Stock Number:**

Illuminating: H201 1370-99-310-0834
 Red: H202 1370-99-702-2071
 Green: H203 1370-99-215-6754
 Yellow: H204 1305-99-184-5674
 White: H208 1370-99-453-6439

UN Number: 0054

Proper Shipping Name: Cartridges, Signal

H201

Qty per Box	Box Type	Hazard Class	NEQ	GR Wgt	Vol
240	Plywood	1.3G	6.24kg	16.50kg	0034m ³

H202

Qty per Box	Box Type	Hazard Class	NEQ	GR Wgt	Vol
240	Plywood	1.3G	5.76kg	15.70kg	0034m ³

H203

Qty per Box	Box Type	Hazard Class	NEQ	GR Wgt	Vol
240	Plywood	1.3G	5.76kg	16.30kg	0034m ³

Content of this informational Data Sheet is subject to modification without prior notice. It does not constitute a Technical Specification.

Chemring Defence UK

Wilne Mill, Draycott, Derbyshire, DE72 3QJ, UK
 Tel: +44 (0)1332 871100 Fax: +44 (0)1332 873046

Chemring Defence Germany GmbH

Vieländer Weg 147, 27574 Bremerhaven, Germany
 Tel:+49 (0) 471 393 0 Fax:+49 (0) 471 393 94
www.chemringdefence.com

Chemring Defence Spain

Pirotecnica Oroquieta S.L. Apartado 124, 31080 Pamplona
 Tel: +34 948 317862 Email: admon@p-oroquieta.com



H204

Qty per Box	Box Type	Hazard Class	NEQ	GR Wgt	Vol
240	Plywood	1.3G	5.28kg	15.90kg	0.034m ³

H205

Qty per Box	Box Type	Hazard Class	NEQ	GR Wgt	Vol
240	Plywood	1.3G	1.68kg	15.50kg	0.034m ³

H206

Qty per Box	Box Type	Hazard Class	NEQ	GR Wgt	Vol
240	Plywood	1.3G	2.45kg	15.90kg	0.034m ³

H207

Qty per Box	Box Type	Hazard Class	NEQ	GR Wgt	Vol
240	Plywood	1.3G	5.59kg	16.50kg	0.034m ³

H208

Qty per Box	Box Type	Hazard Class	NEQ	GR Wgt	Vol
240	Plywood	1.3G	5.28kg	16.50kg	0.034m ³

Content of this informational Data Sheet is subject to modification without prior notice. It does not constitute a Technical Specification.

Chemring Defence UK

Wilne Mill, Draycott, Derbyshire, DE72 3QJ, UK
Tel: +44 (0)1332 871100 Fax: +44 (0)1332 873046

Chemring Defence Germany GmbH

Vieländer Weg 147, 27574 Bremerhaven, Germany
Tel: +49 (0) 471 393 0 Fax: +49 (0) 471 393 94
www.chemringdefence.com

Chemring Defence Spain

Pirotecnica Oroquieta S.L. Apartado 124, 31080 Pamplona
Tel: +34 948 317862 Email: admon@p-oroquieta.com

V2



Part of the Chemring Group

Approved to ISO 9001. Registered in England No. 464142.
Registered Office: Chemring House, 1500 Parkway, Fareham,
Hampshire PO15 7AF. United Kingdom